

R1-AD Smart ADSL2+ IP DSLAM



R1-AD48A

Product Overview

R1-AD series is an ADSL2+ pizza-box type IP DSLAM designed for use in cabinets, vaults or buildings outside of the Central Office that demands a high performance in compact footprint. Available in two port configurations and associated variations in support of last mile loop conditions, R1-AD series has four products: 24 port model with POTS splitters integrated in Annex A (R1-AD24A) and Annex B (R1-AD24B) or a 48 port box (R1-AD48) without splitters in Annex A (R1-AD48A) and Annex B (R1-AD48B). All R1-AD series products are offered in compact, one rack unit entity that is ideal for a variety of applications and service needs. Also the full front access features of R1-AD product give a favor or easy installation and management.

Designed on standards compliant DMT ADSL2+, the R1-AD series delivers up to 24 Mbps downstream bandwidth over Cat.3, UTP copper phone lines. With growing demand for broadcast and on demand video services along with high speed Internet access, the availability of ADSL2+ enables service providers to offer enough bandwidth while enjoying extended rates and reach over ADSL.

R1-AD series offers a wide range of uplink interfaces to choose from, which are supported on IP backbone networks. Dual port Gigabit Ethernet interfaces like 1000BaseT/SX/LX, an EPON and Gigabit Ethernet interface and two 100 Base-FX/TX uplinks are offered. This versatile uplink options allow service providers to use the R1-AD series for high-speed data only with lower speed uplinks, or for video triple play services with the larger capacity uplinks, or capacity scaling in the future.

For video triple play services, R1-AD series has the IP functionalities built-in to support broadcast and VoD service such as IGMP V2 snooping, 802.1q QoS/VLAN tagging and 802.1p CoS.

The compact design of the unit can be used in either 19" rack with selection of AC or DC power. As it is a self-contained unit, with ventilation on both sides, the R1-AD series is easy to install and can be mounted with very limited space utilization in a cabinet or building.

R1-AD series products also support backward ADSL technology compatibility.

Key Features

Platform for deployment everywhere within network

- Compact form factor of 1RU height and 240mm depth
- Full front access for installation, configuration & management
- Temperature hardened version in plan

Provides standard compliant high speed ADSL

- Maximum downstream data rates up to 24 Mbps
- Compliant with ANSI T1.413 issue2, ITU-T G.992.1, G.992.2, G.992.3, G.992.4, G.992.5, G.994.1
- Operable over UTP, CPEV, TIV, SH and Interphone Cable

Advanced port control features

- Per port enable/disable, per port maximum connection rate setting
- Packet forwarding enable/disable function between lines
- Per port IP / MAC filtering

Robust QoS and IGMP snooping support for efficient multicast video and voice over packet delivery

Wide choice of uplink options for various network environment

- Gigabit Ethernet or Gigabit EPON for fiber backhaul network

Scalable role out configurations from 24 port box to mid-capacity cascading through Gigabit Copper connection

Remote upgrade, provisioning and management capabilities through TFTP, FTP, CLI, SNMP, RMON, Telnet or ViewlinX™, EMS

Specifications

INTERFACES

- R1-AD24A/R1-AD24B : 24 port ADSL2+ DSLAM with RJ21 connectors
- R1-AD48A/R1-AD48B : 48 port ADSL2+ DSLAM with RJ21 connectors
- Uplink: SFP gigabit Ethernet supporting fiber, RJ45 gigabit Ethernet supporting copper, SC gigabit EPON supporting fiber.

ADSL Standard

- Modulation/Demodulation: Discrete Multi-Tone(DMT)
- ANSI T1.413 issue2, ITU-T G.992.1/G.992.2/G.992.3/G.992.4 /G.992.5 Annex A & Annex B, ITU-TG.994.1, ATM Forum TM4.1

LAYER 2+ FUNCTIONALITY

- IEEE 802.1p/q
- VLAN, VLAN/VCC mapping, DHCP option 82, IGMP snooping

MANAGEMENT FUNCTIONALITY

- SNMP v1 and v2c, RMON 4 Groups
- Telnet, FTP, TFTP
- SSH2, Radius authentication, TACTACS+ for login access control (Contact for availability)

PHYSICAL SPECIFICATIONS

- R1-AD (W × H × D) : 440mm(17.3 inch) × 44mm(1.73 inch, 1 RU) × 240mm(9.45 inch)
- Power : 100 to 240 VAC (auto-ranging), 50 to 60 Hz for AC
-48 VDC for DC
- Full front access
- Weight : TBD
- Slot configuration : 1 expansion slot

ENVIRONMENTAL & REGULATORY COMPLIANCE

- Operating Temperature (Commercial Version) 0 °C ~ 50 °C
- Operating Relative Humidity: 10 ~ 95% @40 °C, Non-condensing
- MIC, VCCI, CE, UL, FCC Part 15, FCC Part 68 (All planned)

Product Ordering

R1-AD

- R1-AD24A/24B : 24 ports ADSL2+ DSLAM with 1 option slot & embedded splitter, Annex A/Annex B
- R1-AD48A/48B : 48 ports ADSL2+ DSLAM with 1 option slot, Annex A/Annex B
- DC version is also available. Contact CORECESS sales representative for ordering info.

Expansion modules for R1-AD

- OPT-N2CS : 2 port modular SFP 1000Base-FX and RJ45 10/100/1000Base-T gigabit Ethernet combo module
- OPT-N1ES1CS : 1 port 1000Base-PX/10 SC gigabit EPON and 1 port modular SFP 1000Base-FX and RJ45 10/100/1000Base-T gigabit Ethernet combo module

Corecess Inc.

500-2 Sangdaewon-Dong Jungwon-Gu Sungnam-Si Kyonggi, Korea 462-120

Tel : +82-31-739-6600

http://www.corecess.com

• North America

46714 Fremont Boulevard Fremont, CA 94538-6538

Tel.: (510) 683-0188

Fax: (510) 683-0192

800# : (800) 430-9808

Sales : corecess_usa@corecess.com

• China

Room 1602, 889 Renmin Road Shanghai 200010, China.

Tel: +86-21-6350 6699

Fax: +86-21-6351 0880

Sales : corecess_china@corecess.com

• Japan

APOTECH Building 6F, 1-9-1 Nihonbashi-Kakigaracho, Chuo-ku, Tokyo, Japan 103-0014

Tel.: +81-3-3249-0221

Fax : +81-3-3249-0218

Sales : corecess_japan@corecess.com

• Europe

Brovagen 1 182 76 Stocksund/STOCKHOLM SWEDEN

Tel: +46 8 5250 9150

Fax: +46 8 624 32 99

Sales : corecess_eu@corecess.com

• Middle East

Room 1004 Al-Moosa tower 2, Dubai UAE, P.O.Box 112586

Tel.: +971-4-332-4447

Fax : +971-4-329-0892

Sales : corecess_me@corecess.com

• Russia

Park Place Moscow Office D207 113/1 Leninsky Prospect Moscow 117198 Russia

Tel: +7 095 956 5671

+7-095-956-5673

Fax: +7 095 956 5676

Sales : corecess_russia@corecess.com